

superior.



Superior bikes are being developed, designed, tested and built in the heart of Europe, in Kopřivnice, Beskydy Mountains. Our team consists of bike enthusiasts, proper racers and experts, who have been developing top racing bikes for decades. Our motto **#alwaysrace** really shows what our bikes are about, although racing is not the only goal. Every bike we build has to be Superior in every aspect: it has to be light, fast, easy to handle, reliable and also, comfortable.

Superior Bikes werden im Herzen Europas, in Kopřivnice, in den tschechischen Beskiden, entwickelt, konstruiert, getestet und gebaut. Unser Team besteht aus Fahrradenthusiasten, echten Rennfahrern und Experten, die seit Jahrzehnten Top Fahrräder entwickeln. Unser Motto **#alwaysrace** zeigt wirklich, worum es bei unseren Fahrrädern geht, obwohl der Rennsport nicht das einzige Ziel ist. Jedes Rad, das wir bauen, muss in jeder Hinsicht Superior sein: Es muss leicht, schnell, einfach zu handhaben, zuverlässig und auch komfortabel sein.



XF 9.9 Team

Gloss Red Carbon / Black

MTB FULL-SUSPENSION / XF TEAM



SPECIFICATION

ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox SID Ultimate Charger RD 2, Tapered, DebonAir+, 3 Position, 15x110mm axle, 110mm travel
REAR SHOCK	RockShox SIDLuxe Ultimate Remote, size 190x40mm
BOTTOM BRACKET	SRAM DUB, PressFit, shell 41x92 mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SRAM AXS ROCKER, 12-speed
REAR DERAILLEUR	SRAM XX EAGLE AXS T-Type
CRANKSET	SRAM XX, DUB, Carbon, T-Type, 36T
CASSETTE	SRAM XX XS-1299, 12-speed, T-Type, 10-52T
CHAIN	SRAM XX, T-Type

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XTR M9100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT900, 180mm
BRAKE REAR	SHIMANO XTR M9100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT900, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XRC 1501 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1501 SPLINE®, Carbon, CL, 12x148mm, SRAM XD, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ray Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed
TYRE REAR	Schwalbe Racing Ralph Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X1, Carbon
SEAT POST LEVER	SRAM AXS ROCKER, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
HANDLEBAR (MM)	760/60	760/60	760/80	760/80
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	125	125	150	150

XF 9.6 Team

Gloss Carbon / Red Carbon

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XT SW-M8250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8200, 34T
CASSETTE	SHIMANO XT CS-M8200, 12-speed, 10-51T
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8200, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 180mm
BRAKE REAR	SHIMANO XT M8200, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XRC 1700 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1700 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed
TYRE REAR	Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
HANDLEBAR (MM)	760/60	760/60	760/80	760/80
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XF 9.6 RC

Gloss Red / Black

MTB FULL-SUSPENSION / XF RC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x40mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1306S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO M6100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
STEM (MM)	70	70	80	90
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XF 9.2 RC

Matte Carbon / White

MTB FULL-SUSPENSION / XF RC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01, Carbon MTB Race Pro, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
BB DROP (MM)	40	40	40	40
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
STACK HEIGHT (MM)	579	589	597	607
REACH (MM)	427	449	465	482
SEAT TUBE ANGLE	74,9°	74,7°	74,6°	74,5°
HEAD TUBE ANGLE	68°	68°	68°	68°
REAR CENTER (MM)	428	428	428	428
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1124	1149	1169	1189
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XF 9.6 DC

Matte Carbon / Grey

MTB FULL-SUSPENSION / XF DC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01.2, Carbon MTB DC, Advanced Down Country Geometry, Travel 130 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XF 9.2 DC

Matte Mustard

MTB FULL-SUSPENSION / XF DC



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01, Carbon MTB Trail, Advanced Trail Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost 12x148 mm, Inner Cable Routing, dropper seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 130mm travel
REAR SHOCK	AF2 - Twin, LockOut Lever, size 190x51mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
BB DROP (MM)	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
STACK HEIGHT (MM)	589	600	608	617
REACH (MM)	407	429	449	465
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	428	428	428	428
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1154	1180	1200	1220
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XF 6.6 DC

Matte Green Grey

MTB FULL-SUSPENSION / XF DC



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-02-02, Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8220, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XF 6.2 DC

Gloss Olive

MTB FULL-SUSPENSION / XF DC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-02-02, Alu X6 Ultimate MTB Trail SU-02-2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox PSYLO Silver RC, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 9.6

Matte Carbon / Red Carbon

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1306S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SW-M6250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7100, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO M6100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

WHEELSET FRONT	DT Swiss X 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss X 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed
TYRE REAR	Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	57	57	57	57
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	590	615	635	645
STACK HEIGHT (MM)	599	603	613	622
REACH (MM)	435	455	475	495
SEAT TUBE ANGLE	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	95	105	115
WHEELBASE (MM)	1147	1169	1193	1217
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 9.2

Matte Carbon / Dark Chrome

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-781, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SW-M6250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6250-SGS
CRANKSET	SHIMANO FC-MT510, 32T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i25, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i25, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31,8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	57	57	57	57
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	590	615	635	645
STACK HEIGHT (MM)	599	603	613	622
REACH (MM)	435	455	475	495
SEAT TUBE ANGLE	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	95	105	115
WHEELBASE (MM)	1147	1169	1193	1217
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 6.6

Matte Brushed Alu / Black

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212 R5, ZS44/28.6 - ZS56/40
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8100, Hollowtech II, 34T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Terra Aidon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-904A, 31,8mm, Full CNC mached, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
BB DROP (MM)	55	55	55	55
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
STACK HEIGHT (MM)	591	600	609	619
REACH (MM)	415	437	455	472
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	440	440	440	440
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1105	1130	1151	1172
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 6.2

Gloss Brushed Alu / Red

MTB HARDTAIL / XP



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212 R5, ZS44/28.6 - ZS56/40
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Terra Aidon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-904A, 31,8mm, Full CNC mached, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
BB DROP (MM)	55	55	55	55
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
STACK HEIGHT (MM)	591	600	609	619
REACH (MM)	415	437	455	472
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	440	440	440	440
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1105	1130	1151	1172
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 6.1

Matte Grey / Black

MTB HARDTAIL / XP



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212 R5, ZS44/28.6 - ZS56/40
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M5100-IR, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100, Shadow Plus Design
CRANKSET	ONE Race, Alloy, 34T
CASSETTE	SHIMANO DEORE CS-M5100, 11-speed, 11-51T
CHAIN	KMC X11 Grey

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	Schwalbe Rapid Rob, KevlarGuard, 29x2.10
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	Schwalbe Rapid Rob, KevlarGuard, 29x2.10
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Terra Aidon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-904A, 31,8mm, Full CNC mached, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
BB DROP (MM)	55	55	55	55
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
STACK HEIGHT (MM)	591	600	609	619
REACH (MM)	415	437	455	472
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	440	440	440	440
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1105	1130	1151	1172
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 899

MATTE OLIVE METALLIC

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Aerial, 1-1/8", 120mm travel
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M5100-R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT5100-1, 32T
CASSETTE	SHIMANO DEORE CS-M5100, 11-speed, 11-51T
CHAIN	KMC X11 Grey

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	615	634	634	653
REACH (MM)	393	408	428	443
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	100	120	120	140
WHEELBASE (MM)	1096	1119	1139	1160
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	740	740	740	740
CRANKSET (MM)	170	175	175	175

XC 889 W

GLOSS WHITE METALLIC

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Aerial, 1-1/8", 100mm travel
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS LEFT	SHIMANO DEORE SL-M5100-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO DEORE SL-M5100-R, RAPIDFIRE Plus, 11-speed
FRONT DERAILLEUR	SHIMANO DEORE FD-M5100-M, Side Swing, Front Pull
REAR DERAILLEUR	SHIMANO DEORE RD-M4120, Shadow Design
CRANKSET	SHIMANO FC-M5100-2, 36-26T
CASSETTE	SHIMANO DEORE CS-M5100, 11-speed, 11-42T
CHAIN	KMC X11 Grey

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	60	60
SEAT TUBE LENGTH (MM)	406	457
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
STACK HEIGHT (MM)	615	634
REACH (MM)	393	408
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	100	120
WHEELBASE (MM)	1096	1119
STEM (MM)	70	70
HANDLEBAR (MM)	720	720
CRANKSET (MM)	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 879

MATTE PETROL

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Aerial, 1-1/8", 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT501, BSA, shell 68/73mm
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS LEFT	SHIMANO DEORE SL-M5100-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed
FRONT DERAILLEUR	SHIMANO DEORE FD-M4100-M, Side Swing, Front Pull
REAR DERAILLEUR	SHIMANO DEORE RD-M4120, Shadow Design
CRANKSET	ONE Race, Alloy, 36-26T
CASSETTE	SHIMANO DEORE CS-M4100, 10-speed, 11-42T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	615	634	634	653
REACH (MM)	393	408	428	443
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	100	120	120	140
WHEELBASE (MM)	1096	1119	1139	1160
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	740	740	740	740
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 879 W

GLOSS BLACK RAINBOW

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Aerial, 1-1/8", 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT501, BSA, shell 68/73mm
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS LEFT	SHIMANO DEORE SL-M5100-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed
FRONT DERAILLEUR	SHIMANO DEORE FD-M4100-M, Side Swing, Front Pull
REAR DERAILLEUR	SHIMANO DEORE RD-M4120, Shadow Design
CRANKSET	ONE Race, Alloy, 36-26T
CASSETTE	SHIMANO DEORE CS-M4100, 10-speed, 11-42T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	615	634	634
REACH (MM)	393	408	428
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	442	442	442
HEAD TUBE LENGTH (MM)	100	120	120
WHEELBASE (MM)	1096	1119	1139
STEM (MM)	70	70	90
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	175
SEATPOST (MM)	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Blaze, 1-1/8", 120mm travel
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M4120, Shadow Design
CRANKSET	SHIMANO FC-MT5100-1, 32T
CASSETTE	SHIMANO DEORE CS-M4100, 10-speed, 11-42T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	615	634	634	653
REACH (MM)	393	408	428	443
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	100	120	120	140
WHEELBASE (MM)	1096	1119	1139	1160
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	740	740	740	740
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	350	350	350	350

XC 819

GLOSS DARK RED

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Blaze, 1-1/8", 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ALTUS SL-M315-2L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
FRONT DERAILLEUR	SHIMANO ALTUS FD-M315-TS, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-M315-2, 36-22T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TX505, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-TX505-8, 32H, CL, M10x135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	615	634	634
REACH (MM)	393	408	428
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	442	442	442
HEAD TUBE LENGTH (MM)	100	120	120
WHEELBASE (MM)	1096	1119	1139
STEM (MM)	70	70	90
HANDLEBAR (MM)	740	740	740
CRANKSET (MM)	170	175	175
SEATPOST (MM)	350	350	350

XC 819

GLOSS COPPER

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Blaze, 1-1/8", 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ALTUS SL-M315-2L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
FRONT DERAILLEUR	SHIMANO ALTUS FD-M315-TS, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-M315-2, 36-22T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TX505, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-TX505-8, 32H, CL, M10x135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	615	634	634	653
REACH (MM)	393	408	428	443
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	100	120	120	140
WHEELBASE (MM)	1096	1119	1139	1160
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	740	740	740	740
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 819 W

GLOSS WHITE METALLIC

MTB HARDTAIL / XC



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	RST Blaze, 1-1/8", 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ALTUS SL-M315-2L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
FRONT DERAILLEUR	SHIMANO ALTUS FD-M315-TS, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-M315-2, 36-22T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TYRE FRONT	CST Jack Rabbit, 29x2.25"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TYRE REAR	CST Jack Rabbit, 29x2.25"
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -8°
HANDLEBAR	ONE Alloy, 12mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	60	60
SEAT TUBE LENGTH (MM)	406	457
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
STACK HEIGHT (MM)	615	634
REACH (MM)	393	408
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	100	120
WHEELBASE (MM)	1096	1119
STEM (MM)	70	70
HANDLEBAR (MM)	720	720
CRANKSET (MM)	170	170
SEATPOST (MM)	350	350

XR 9.8 GF

Gloss Carbon / Grey

ROAD & GRAVEL / GRAN FONDO



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Hi Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-72-41B, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ULTEGRA R8170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO ULTEGRA R8170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO ULTEGRA RD-R8150, Shadow Design
CRANKSET	SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T
CASSETTE	SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKE REAR	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ERC 1400 DICUT®, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ERC 1400 DICUT®, Carbon, CL, 12x142mm, SH11, Tubeless Ready
TYRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	77	77	77	77
SEAT TUBE LENGTH (MM)	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (MM)	532	545	569	591
STACK HEIGHT (MM)	537	557	578	597
REACH (MM)	376	380	392	408
SEAT TUBE ANGLE	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71°	71,5°	71,5°	72°
REAR CENTER (MM)	415	415	415	415
HEAD TUBE LENGTH (MM)	120	140	160	180
WHEELBASE (MM)	995	1000	1016	1034
HANDLEBAR (MM)	380/90	400/100	400/100	420/110
CRANKSET (MM)	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.7 GF

Gloss Carbon Red

ROAD & GRAVEL / GRAN FONDO



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Hi Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-72-41B, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ULTEGRA R8170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO ULTEGRA R8170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO ULTEGRA RD-R8150, Shadow Design
CRANKSET	SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T
CASSETTE	SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKE REAR	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ER 1600 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ER 1600 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready
TYRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	520mm (S)540mm (M)560mm (L)580mm (XL)			
BB DROP (MM)	77	77	77	77
SEAT TUBE LENGTH (MM)	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (MM)	532	545	569	591
STACK HEIGHT (MM)	537	557	578	597
REACH (MM)	376	380	392	408
SEAT TUBE ANGLE	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71°	71,5°	71,5°	72°
REAR CENTER (MM)	415	415	415	415
HEAD TUBE LENGTH (MM)	120	140	160	180
WHEELBASE (MM)	995	1000	1016	1034
HANDLEBAR (MM)	380/90	400/100	400/100	420/110
CRANKSET (MM)	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.5 GF

Gloss Grey / Red

ROAD & GRAVEL / GRAN FONDO



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	SU-52-01, Carbon XR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7150, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7100, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7170, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7170, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

WHEELSET FRONT	DT Swiss E 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss E 1800 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready
TYRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	77	77	77	77
SEAT TUBE LENGTH (MM)	440	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	525	532	545	569	591	610
STACK HEIGHT (MM)	517	537	557	578	597	605
REACH (MM)	370	376	380	392	408	417
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°	72,5°
HEAD TUBE ANGLE	71°	71°	71,5°	71,5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	994	995	1000	1016	1034	1048
STEM (MM)	70	80	100	100	110	110
HANDLEBAR (MM)	410	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	400	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 6.5 GF

Matte Black Stealth

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7120, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7100, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRE FRONT	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRE REAR	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	500mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	523	530	540	570	590
STACK HEIGHT (MM)	549	558	569	606	616
REACH (MM)	368	367	371	384	401
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71,5°	71,5°	72°	73°	73°
REAR CENTER (MM)	414	414	414	414	414
HEAD TUBE LENGTH (MM)	125	135	145	180	190
WHEELBASE (MM)	990	992	995	1010	1030
STEM (MM)	70	80	100	100	110
HANDLEBAR (MM)	410	410	410	410	430
CRANKSET (MM)	165	165	170	172.5	172.5

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

X-ROAD 6.3 GF

Gloss Grey / Black

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO TIAGRA R-4720, 2-speed
SHIFTERS RIGHT	SHIMANO TIAGRA R-4720, 10-speed
FRONT DERAILLEUR	SHIMANO TIAGRA FD-4700, Brazed-On Type
REAR DERAILLEUR	SHIMANO TIAGRA RD-4700
CRANKSET	SHIMANO FC-RS400, 50-34T
CASSETTE	SHIMANO CS-HG500, 10-speed, 11-34T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO TIAGRA R-4720, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKE REAR	SHIMANO TIAGRA R4720, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J22GT, Disc, 28H
TYRE FRONT	Schwalbe Lugano II, KevlarGuard, 32-622
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J22GT, Disc, 28H
TYRE REAR	Schwalbe Lugano II, KevlarGuard, 32-622
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	500mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	523	530	540	570	590
STACK HEIGHT (MM)	549	558	569	606	616
REACH (MM)	368	367	371	384	401
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71,5°	71,5°	72°	73°	73°
REAR CENTER (MM)	414	414	414	414	414
HEAD TUBE LENGTH (MM)	125	135	145	180	190
WHEELBASE (MM)	990	992	995	1010	1030
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	410	430
CRANKSET (MM)	170	170	170	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.9 GR

Matte Carbon / Gloss Red

ROAD & GRAVEL / GRAVEL



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Hi Modulus Carbon Fork
BOTTOM BRACKET	SRAM DUB ROAD WIDE, PressFit, shell 41x86,5 mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS LEFT	SRAM RED AXS, electronic shifter
SHIFTERS RIGHT	SRAM RED AXS, electronic shifter
REAR DERAILLEUR	SRAM RED XPLR AXS, 13 speed
CRANKSET	SRAM RED XPLR, DUB WIDE, 44T
CASSETTE	SRAM RED XPLR XG-1391, 13-speed, 10-46T
CHAIN	SRAM RED, Flattop

BRAKING SYSTEM

BRAKE FRONT	SRAM RED AXS, hydraulic disc brake
ROTOR FRONT	SRAM Paceline X, 160mm
BRAKE REAR	SRAM RED AXS, hydraulic disc brake
ROTOR REAR	SRAM Paceline X, 140mm

WHEELS

WHEELSET FRONT	DT Swiss GRC 1600, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss GRC 1600, Carbon, CL, 12x142mm, XDR, Tubeless Ready
TYRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
TYRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	520mm (S)540mm (M)560mm (L)580mm (XL)			
BB DROP (MM)	77	77	77	77
SEAT TUBE LENGTH (MM)	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (MM)	532	545	569	591
STACK HEIGHT (MM)	537	557	578	597
REACH (MM)	376	380	392	408
SEAT TUBE ANGLE	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71°	71,5°	71,5°	72°
REAR CENTER (MM)	415	415	415	415
HEAD TUBE LENGTH (MM)	120	140	160	180
WHEELBASE (MM)	995	1000	1016	1034
HANDLEBAR (MM)	380/70	420/90	420/90	440/100
CRANKSET (MM)	165	170	172,5	172,5
SEATPOST (MM)	400	400	400	400

XR 9.7 GR

Gloss Grey / Racing Yellow

ROAD & GRAVEL / GRAVEL



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Hi Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX820, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX820, Hollowtech II, 42T
CASSETTE	SHIMANO XT CS-M8100, 12-speed, 10-45T
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX820, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKE REAR	SHIMANO GRX RX820, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 140mm

WHEELS

WHEELSET FRONT	DT Swiss GR 1600 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss GR 1600 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
TYRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	77	77	77	77
SEAT TUBE LENGTH (MM)	440	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	525	532	545	569	591	610
STACK HEIGHT (MM)	517	537	557	578	597	605
REACH (MM)	370	376	380	392	408	417
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°	72,5°
HEAD TUBE ANGLE	71°	71°	71,5°	71,5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	994	995	1000	1016	1034	1048
HANDLEBAR (MM)	380/70	380/70	420/90	420/90	440/100	440/100
CRANKSET (MM)	170	170	170	172.5	172.5	175
SEATPOST (MM)	400	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.5 GR

Matte Green Grey / Green

ROAD & GRAVEL / GRAVEL



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	SU-52-01, Carbon XR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

WHEELSET FRONT	DT Swiss G 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss G 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
TYRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	77	77	77	77
SEAT TUBE LENGTH (MM)	440	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	525	532	545	569	591	610
STACK HEIGHT (MM)	517	537	557	578	597	605
REACH (MM)	370	376	380	392	408	417
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°	72,5°
HEAD TUBE ANGLE	71°	71°	71,5°	71,5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	994	995	1000	1016	1034	1048
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	400	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 6.5 GR

Matte Mustard / Black

ROAD & GRAVEL / GRAVEL



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-42T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12X142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	500mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	523	530	540	570	590
STACK HEIGHT (MM)	549	558	569	606	616
REACH (MM)	368	367	371	384	401
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71,5°	71,5°	72°	73°	73°
REAR CENTER (MM)	414	414	414	414	414
HEAD TUBE LENGTH (MM)	125	135	145	180	190
WHEELBASE (MM)	990	992	995	1010	1030
STEM (MM)	70	70	80	80	100
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 6.4 GR

Matte Green Grey / Black

ROAD & GRAVEL / GRAVEL



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO GRX RX400, 2-speed
SHIFTERS RIGHT	SHIMANO GRX RX400, 10-speed
FRONT DERAILLEUR	SHIMANO GRX FD-RX400, Brazed-On Type
REAR DERAILLEUR	SHIMANO GRX RD-RX400, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX600, 46-30T
CASSETTE	SHIMANO CS-HG500, 10-speed, 11-34T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX400, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX400, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J22GT, Disc, 28H
TYRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J22GT, Disc, 28H
TYRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	500mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	523	530	540	570	590
STACK HEIGHT (MM)	549	558	569	606	616
REACH (MM)	368	367	371	384	401
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71,5°	71,5°	72°	73°	73°
REAR CENTER (MM)	414	414	414	414	414
HEAD TUBE LENGTH (MM)	125	135	145	180	190
WHEELBASE (MM)	990	992	995	1010	1030
STEM (MM)	70	70	80	80	100
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

TEAM 27 Issue

MATTE BLACK

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru axle 148x12mm, Inner cable routing.
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212.R5, ZS44/28.6 - ZS56/40
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	ONE Race, Alloy, 165mm, 32T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 28H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J20S, Disc, 28H
TYRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 28H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J20S, Disc, 28H
TYRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEAT POST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
STACK HEIGHT (MM)	570	570
REACH (MM)	382	423
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	418	418
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1048	1089
HANDLEBAR (MM)	660/45	660/45
CRANKSET (MM)	160	165

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

TEAM 27 Elite

GLOSS DARK RED

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, SR dropout, Inner cable routing
SUSPENSION FORK	RST Aerial, 1-1/8", 100mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5120, Shadow Plus Design
CRANKSET	ONE Sport, Alloy, 160mm, 32T
CASSETTE	SHIMANO DEORE CS-M4100, 10-speed, 11-46T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J20S, Disc, 28H
TYRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	ONE Sport, 28H, CL, M10x135, QR Type
RIM REAR	STARS J20S, Disc, 28H
TYRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	13.5" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
HANDLEBAR (MM)	660/45	660/45
CRANKSET (MM)	160	160

TEAM 27 Elite

MATTE BLACK

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, SR dropout, Inner cable routing
SUSPENSION FORK	RST Aerial, 1-1/8", 100mm travel
BOTTOM BRACKET	Thun Ibcx, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5120, Shadow Plus Design
CRANKSET	ONE Sport, Alloy, 160mm, 32T
CASSETTE	SHIMANO DEORE CS-M4100, 10-speed, 11-46T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J20S, Disc, 28H
TYRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	ONE Sport, 28H, CL, M10x135, QR Type
RIM REAR	STARS J20S, Disc, 28H
TYRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	13.5" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
HANDLEBAR (MM)	660/45	660/45
CRANKSET (MM)	160	160

Team 24

GLOSS DARK RED

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Race Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount,
SUSPENSION FORK	RST Aerial Air, 1-1/8", 60mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SRAM X5, Trigger Shifter, 9-speed
REAR DERAILLEUR	SRAM X7
CRANKSET	ONE Sport, Alloy, 140mm, 28T
CASSETTE	SHIMANO CS-HG201, 9-speed, 11-36T
CHAIN	KMC X9

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	ALHONGA, 160mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	ALHONGA, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J18SF, Disc, 20H
TYRE FRONT	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J18SF, Disc, 20H
TYRE REAR	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-400

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	25
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	500
REACH (MM)	347
SEAT TUBE ANGLE	73°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	971
HANDLEBAR (MM)	580/45
CRANKSET (MM)	140

Team 24

MATTE BLACK

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Race Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount,
SUSPENSION FORK	RST Aerial Air, 1-1/8", 60mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SRAM X5, Trigger Shifter, 9-speed
REAR DERAILLEUR	SRAM X7
CRANKSET	ONE Sport, Alloy, 140mm, 28T
CASSETTE	SHIMANO CS-HG201, 9-speed, 11-36T
CHAIN	KMC X9

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	ALHONGA, 160mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	ALHONGA, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J18SF, Disc, 20H
TYRE FRONT	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J18SF, Disc, 20H
TYRE REAR	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-400

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	25
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	500
REACH (MM)	347
SEAT TUBE ANGLE	73°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	971
HANDLEBAR (MM)	580/45
CRANKSET (MM)	140

Team 20

MATTE BLACK

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount,
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CLARIS SL-R2000, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	ONE Sport, Alloy, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-32T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	ALHONGA, 140mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	ALHONGA, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J18SF, Disc, 20H
TYRE FRONT	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J18SF, Disc, 20H
TYRE REAR	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Junior
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-202

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	0
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	379
REACH (MM)	327
SEAT TUBE ANGLE	72°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	859
HANDLEBAR (MM)	560/45
CRANKSET (MM)	127

Team 20

GLOSS DARK RED

JUNIOR / TEAM



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount,
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CLARIS SL-R2000, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	ONE Sport, Alloy, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-32T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	ALHONGA, 140mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	ALHONGA, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J18SF, Disc, 20H
TYRE FRONT	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J18SF, Disc, 20H
TYRE REAR	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

HANDLEBAR	ONE Alloy Integrated Cockpit
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Junior
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-202

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	0
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	379
REACH (MM)	327
SEAT TUBE ANGLE	72°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	859
HANDLEBAR (MM)	560/45
CRANKSET (MM)	127

RACER XC 27 DB

MATTE LIME

JUNIOR / RACER



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCT30, 1-1/8", Coil, QR Type, 100mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ACERA RD-M3020
CRANKSET	ONE Sport, Alloy, 160mm, 32T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TX505, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J20S, Disc, 32H
TYRE FRONT	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
HUB REAR	SHIMANO FH-TX505-8, 32H, CL, M10x135mm, QR Type
RIM REAR	STARS J20S, Disc, 32H
TYRE REAR	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 34mm rise, 25.4mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-610

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	435	435
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
STEM (MM)	35	35
HANDLEBAR (MM)	600	600
CRANKSET (MM)	160	160

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

RACER XC 24

GLOSS WHITE

JUNIOR / RACER



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCT JR24, 1-1/8", Soft Spring, QR Type, 50mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH290TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, 140mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	Saccon Junior, V-Brake
BRAKE REAR	Saccon Junior, V-Brake

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TYRE FRONT	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
HUB REAR	ONE Sport, 24H, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TYRE REAR	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Junior
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-400

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	25
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	73°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	974
STEM (MM)	35
HANDLEBAR (MM)	540
CRANKSET (MM)	140

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

RACER XC 24

MATTE LIME

JUNIOR / RACER



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCT JR24, 1-1/8", Soft Spring, QR Type, 50mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH290TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, 140mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	Saccon Junior, V-Brake
BRAKE REAR	Saccon Junior, V-Brake

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TYRE FRONT	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
HUB REAR	ONE Sport, 24H, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TYRE REAR	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Junior
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-400

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	25
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	73°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	974
STEM (MM)	35
HANDLEBAR (MM)	540
CRANKSET (MM)	140

RACER XC 20

GLOSS WHITE

JUNIOR / RACER



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout,
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH290TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, 127mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	Saccon Junior, V-Brake
BRAKE REAR	Saccon Junior, V-Brake

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TYRE FRONT	Schwalbe Black Jack, KevlarGuard, 20x1.90
HUB REAR	ONE Sport, 24H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TYRE REAR	Schwalbe Black Jack, KevlarGuard, 20x1.90
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Junior
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-202

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	0
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	375
REACH (MM)	328
SEAT TUBE ANGLE	73°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	828
STEM (MM)	35
HANDLEBAR (MM)	500
CRANKSET (MM)	127

RACER XC 20

MATTE LIME

JUNIOR / RACER



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout,
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH290TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, 127mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8

BRAKING SYSTEM

BRAKE FRONT	Saccon Junior, V-Brake
BRAKE REAR	Saccon Junior, V-Brake

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TYRE FRONT	Schwalbe Black Jack, KevlarGuard, 20x1.90
HUB REAR	ONE Sport, 24H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TYRE REAR	Schwalbe Black Jack, KevlarGuard, 20x1.90
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Junior
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31,8mm, with Quick Release level, Black
PEDALS	Marwi SP-202

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	0
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	375
REACH (MM)	328
SEAT TUBE ANGLE	73°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	828
STEM (MM)	35
HANDLEBAR (MM)	500
CRANKSET (MM)	127

iXF 9.8

Matte Berry Carbon

iMTB FULL SUSPENSION | Light / iXF



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E10-01, Carbon MTB DC; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535, Tapered, 15x110mm axle, 150mm travel
REAR SHOCK	DT Swiss R535, size 210x55mm
HEADSET	ACROS AZX-596S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SRAM AXS POD, 12-speed
REAR DERAILLEUR	SRAM X0 EAGLE AXS T-Type
CRANKSET	SRAM X0, BOSCH
CHAINRING	SRAM T-TYPE, 36T
CASSETTE	SRAM X0 XS-1295, 12-speed, T-Type, 10-52T
CHAIN	SRAM X0, T-Type

BRAKING SYSTEM

BRAKE FRONT	SRAM LEVEL SILVER STEALTH, 4 piston, hydraulic disc brake
ROTOR FRONT	SRAM HS2, 180mm
BRAKE REAR	SRAM LEVEL SILVER STEALTH, 4 piston, hydraulic disc brake
ROTOR REAR	SRAM HS2, 180mm

WHEELS

WHEELSET FRONT	DT Swiss Hybrid MTB HXC 1501 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss Hybrid MTB HXC 1501 SPLINE®, Carbon, CL, 12x148mm, SRAM XD, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SRAM AXS POD, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	32	32	32	32
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301
HANDLEBAR (MM)	760/40	760/40	760/60	760/60
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	125	150		

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

iXF 9.7

Matte Carbon

iMTB FULL SUSPENSION | Light / iXF



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E10-01, Carbon MTB DC; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535, Tapered, 15x110mm axle, 150mm travel
REAR SHOCK	DT Swiss R535, size 210x55mm
HEADSET	ACROS AZX-596S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

WHEELSET FRONT	DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	32	32	32	32
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

iXF 9.2

Matte Mustard

iMTB FULL SUSPENSION | Light / iXF



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E10-01, Carbon MTB DC; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 210x55mm
HEADSET	ACROS AZX-596S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	32	32	32	32
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

iBLOX 6.5

Gloss Grey

iTOUR | Light / iBLOX



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E41-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	642	651	660	670
REACH (MM)	386	403	421	438
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	120	130	140	150
WHEELBASE (MM)	1102	1123	1144	1165
STEM (MM)	65	65	90	90
HANDLEBAR (MM)	700	700	700	700
CRANKSET (MM)	160	165	170	170
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

iBLOX 6.5 Mid Step

Gloss Grey

iTOUR | Light / iBLOX



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E41-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	15" (S)	16" (M)	18" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	381	457	496
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	642	651	660
REACH (MM)	386	403	421
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	450	450	450
HEAD TUBE LENGTH (MM)	120	130	140
WHEELBASE (MM)	1102	1123	1144
STEM (MM)	65	65	65
HANDLEBAR (MM)	660	660	660
CRANKSET (MM)	160	165	170
SEATPOST (MM)	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

iBLOX 6.5 Low Step

Gloss Grey

iTOUR | Light / iBLOX



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E41-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	15" (S)	16" (M)	18" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	365	432	485
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	642	651	660
REACH (MM)	386	403	421
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	450	450	450
HEAD TUBE LENGTH (MM)	120	130	140
WHEELBASE (MM)	1102	1123	1144
STEM (MM)	65	65	65
HANDLEBAR (MM)	660	660	660
CRANKSET (MM)	160	165	170
SEATPOST (MM)	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 6.8

Gloss Olive Metallic / Black

eMTB FULL SUSPENSION / eXF



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535, Tapered, 15x110mm axle, 160mm travel
REAR SHOCK	DT Swiss R535, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE XT SL-M8100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 203mm
BRAKE REAR	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 180mm

WHEELS

WHEELSET FRONT	DT Swiss H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX Soft
TYRE REAR	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX SpeedGrip

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L358/T100	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 6.5

Gloss Copper / Black

eMTB FULL SUSPENSION / eXF



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Super Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27
SEAT TUBE LENGTH (MM)	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	610	630	650
STACK HEIGHT (MM)	625	625	625
REACH (MM)	465	485	505
SEAT TUBE ANGLE	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°
REAR CENTER (MM)	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120
WHEELBASE (MM)	1251	1271	1291
STEM (MM)	50	50	50
HANDLEBAR (MM)	760	760	760
CRANKSET (MM)	165	165	170
SEATPOST (MM)	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 9019 B

Gloss Copper / Black

eMTB FULL SUSPENSION / eXF



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Super Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-R, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-904A, 34,9mm, Full CNC mached, Black

GEOMETRY

FRAME SIZE	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27
SEAT TUBE LENGTH (MM)	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	610	630	650
STACK HEIGHT (MM)	625	625	625
REACH (MM)	465	485	505
SEAT TUBE ANGLE	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°
REAR CENTER (MM)	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120
WHEELBASE (MM)	1251	1271	1291
STEM (MM)	50	50	50
HANDLEBAR (MM)	760	760	760
CRANKSET (MM)	165	165	170
SEATPOST (MM)	L440/T150	L480/T170	L480/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 8089 B

Gloss Chrome / Black

eMTB FULL SUSPENSION / eXF



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Nobby Nic Performance, 29x2.60
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Nobby Nic Performance, 29x2.60
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 8089 B SUV

eMTB FULL SUSPENSION / eXF

Gloss Black / Black



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x57.5mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Johnny Watts Performance, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Johnny Watts Performance, 29x2.35", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	AXA Juno
FENDER	Alloy

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	60	60	60	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	160	160	160	165

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	RockShox RECON Silver RL, Tapered, SoloAir, 15x110mm axle, 120mm travel
HEADSET	ACROS AZX-596S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE, 34.9mm, Black Matte

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1215	1215	1235	1264
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

eXP 6.5

Matte Dark Chrome / Black

eMTB HARDTAIL / eXP



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 600Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 120mm travel
HEADSET	ACROS AZX-596, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 203MM
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE, 34.9mm, Black Matte

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1215	1215	1235	1264
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXP 6.3

Gloss Grey / Red

eMTB HARDTAIL / eXP



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH PX Performance, Battery PowerTube 600Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Intuvia 100

FRAMESET

FRAME	SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCR32, Tapered, 15x110mm axle, 120mm travel
HEADSET	ACROS AZX-596, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Hurricane Performance, 29x2.25, ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Hurricane Performance, 29x2.25, ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1215	1215	1235	1264
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.5 Mid Step

Gloss White / Copper

eTOUR / eBLOX



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SUE05-CXBES3, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Alloy, 20mm rise, 30.9mm
SEATPOST CLAMP	ONE CC-617, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16.5" (S)	18" (M)
BB DROP (MM)	51	51
SEAT TUBE LENGTH (MM)	393	431
EFFECTIVE TOP TUBE LENGTH (MM)	590	610
STACK HEIGHT (MM)	635	653
REACH (MM)	465	465
SEAT TUBE ANGLE	78,9°	77,5°
HEAD TUBE ANGLE	66°	66°
REAR CENTER (MM)	445	445
HEAD TUBE LENGTH (MM)	120	140
WHEELBASE (MM)	1205	1213
STEM (MM)	65	65
HANDLEBAR (MM)	660	660
CRANKSET (MM)	160	160
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.5 Low Step

Matte Dark Chrome / Black

eTOUR / eBLOX



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Marathon Almotion Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Marathon Almotion Performance, RaceGuard, 55-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanningsa Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	51	51
SEAT TUBE LENGTH (MM)	393	431
EFFECTIVE TOP TUBE LENGTH (MM)	590	610
STACK HEIGHT (MM)	635	653
REACH (MM)	465	465
SEAT TUBE ANGLE	78,9°	77,5°
HEAD TUBE ANGLE	66°	66°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	120	140
WHEELBASE (MM)	1205	1213
STEM (MM)	65	65
HANDLEBAR (MM)	700	700

CRANKSET (MM)	160	160
---------------	-----	-----

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.3 Low Step

Matte Green Grey / Green

eTOUR / eBLOX



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH PX Performance, Battery PowerTube 600Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Intuvia 100

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, 15x100mm axle, 80mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DÉRAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x100mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TYRE FRONT	Schwalbe Marathon Almotion Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TYRE REAR	Schwalbe Marathon Almotion Performance, RaceGuard, 55-622
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30,9mm
SEATPOST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanningsa Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	51	51
SEAT TUBE LENGTH (MM)	393	431
EFFECTIVE TOP TUBE LENGTH (MM)	590	610
STACK HEIGHT (MM)	635	653
REACH (MM)	465	465
SEAT TUBE ANGLE	78,9°	77,5°
HEAD TUBE ANGLE	66°	66°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	120	140
WHEELBASE (MM)	1205	1213
STEM (MM)	65	65
HANDLEBAR (MM)	700	700

CRANKSET (MM)	160	160
---------------	-----	-----

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eWAY 6.5

Gloss Grey

eCITY / eWAY



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes)

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuiva 100

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, 1-1/8", QR Type, 50mm travel
HEADSET	ONE PT-1866A-078-2 1-1/8", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO NEXUS SL-C7000-5, REVOSHIFT, 5-speed
CRANKSET	ONE Sport, Alloy
CHAINRING	Gates CARBON DRIVE CDX, 46T
CASSETTE	Gates CARBON DRIVE CDX, 34T
CHAIN	Gates CARBON DRIVE CDX

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	ONE, 36H, Disc, 3/8"x100x140mm, Nut Type
RIM FRONT	STARS J19DC, Disc, 36H
TYRE FRONT	SCALATO MONDANO, 50-622, Reflective Tape
HUB REAR	SHIMANO NEXUS SG-C7000-5D, 36H, CL, 135x187mm
RIM REAR	STARS J19DC, Disc, 36H
TYRE REAR	SCALATO MONDANO, 50-622, Reflective Tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 38mm rise, 31.8mm
GRIPS LEFT	HERRMANS Line DD36
GRIPS RIGHT	HERRMANS Line DD36

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE, Alloy, Suspension, 30,9mm
SEATPOST CLAMP	ONE FR-E04_01, 34,9mm, Black
PEDALS	Marwi SP-828

CITY/ SUV SET

FRONT LIGHT	Spanninga X&O, 50
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)
BB DROP (MM)	62	62	62
SEAT TUBE LENGTH (MM)	460	500	540
EFFECTIVE TOP TUBE LENGTH (MM)	580	600	620
STACK HEIGHT (MM)	604	626	648
REACH (MM)	390	397	403
SEAT TUBE ANGLE	72,5°	72°	71,5°
HEAD TUBE ANGLE	69°	69,8°	70,5°
REAR CENTER (MM)	485	485	485
HEAD TUBE LENGTH (MM)	170	180	190
WHEELBASE (MM)	1127	1133	1139
STEM (MM)	75		
HANDLEBAR (MM)	620	620	620
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eWAY 6.4

Matte Black

eCITY / eWAY



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes)

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, 1-1/8", QR Type, 50mm travel
HEADSET	ONE PT-1866A-078-2 1-1/8", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 44T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J19DC, Disc, 36H
TYRE FRONT	SCALATO MONDANO, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J19DC, Disc, 36H
TYRE REAR	SCALATO MONDANO, 50-622, Reflective Tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 38mm rise, 31.8mm
GRIPS LEFT	HERRMANS Line DD36
GRIPS RIGHT	HERRMANS Line DD36

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE FR-E04_01, 34,9mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	Spanninga X&O, 30
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy
CARRIER	Alloy Carrier with MIK system

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)
BB DROP (MM)	62	62	62
SEAT TUBE LENGTH (MM)	460	500	540
EFFECTIVE TOP TUBE LENGTH (MM)	580	600	620
STACK HEIGHT (MM)	604	626	648
REACH (MM)	390	397	403
SEAT TUBE ANGLE	72,5°	72°	71,5°
HEAD TUBE ANGLE	69°	69,8°	70,5°
REAR CENTER (MM)	485	485	485
HEAD TUBE LENGTH (MM)	170	180	190
WHEELBASE (MM)	1127	1133	1139
STEM (MM)	90	90	110
HANDLEBAR (MM)	620	620	620
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH ACTIVE LINE PLUS; Battery PowerTube 500Wh
DISTANCE	140km
MAX. TORQUE	50Nm / 270%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes)

E- BIKE PARTS

MOTOR	BOSCH Active Line Plus, BES3, 50Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 500Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, 1-1/8", QR Type, 50mm travel
HEADSET	ONE PT-1866A-078-2 1-1/8", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO NEXUS SL-C3000-7 Revoshift, 7-speed
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 38T
CASSETTE	SHIMANO NEXUS, Sprocket, 18T
CHAIN	KMC Z1eHX

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	ONE, 36H, Disc, 3/8"x100x140mm, Nut Type
RIM FRONT	STARS J19DC, Disc, 36H
TYRE FRONT	SCALATO MONDANO, 50-622, Reflective Tape
HUB REAR	SHIMANO NEXUS SG-C3001-7D, 36H, CL, 135x187mm
RIM REAR	STARS J19DC, Disc, 36H
TYRE REAR	SCALATO MONDANO, 50-622, Reflective Tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 38mm rise, 31.8mm
GRIPS LEFT	HERRMANS Line DD36
GRIPS RIGHT	HERRMANS Line DD36

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE Sport, Alloy, 30,9mm
SEATPOST CLAMP	ONE FR-E04_01, 34,9mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	Spanninga X&O, 30
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)
BB DROP (MM)	62	62
SEAT TUBE LENGTH (MM)	460	500
EFFECTIVE TOP TUBE LENGTH (MM)	580	600
STACK HEIGHT (MM)	604	626
REACH (MM)	390	397
SEAT TUBE ANGLE	72,5°	72°
HEAD TUBE ANGLE	69°	69,8°
REAR CENTER (MM)	485	485
HEAD TUBE LENGTH (MM)	170	180
WHEELBASE (MM)	1127	1133
STEM (MM)	75	
HANDLEBAR (MM)	620	620
CRANKSET (MM)	170	170

STK 500 L

GREY

URBAN



COMPUTER VISUALIZATION

GEOMETRY

FRAME SIZE	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	440	483	533
SEAT TUBE ANGLE (DEGREE)	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	580	595	605
REACH (MM)	400	415	425
STACK HEIGHT (MM)	624	624	624
HEAD TUBE LENGTH (MM)	180	180	180
HEAD TUBE ANGLE (DEGREE)	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1102	1117	1127
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Low Entry, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	GREY/GREEN
SIZES	17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed, SHIMANO ALIVIO SL-M3100-L RapidFire Plus, 3-speed
FRONT DERAILLEUR	SHIMANO ACERA FD-T3000, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO ACERA FC-M371, 48-36-26T
CASSETTE	SHIMANO CS-HG200-9, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-153BT, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio
SEAT POST	ONE1 Alloy, SPS 405, 27.2mm

WHEELS

FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENETR LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 500

GREY

URBAN



COMPUTER VISUALIZATION

GEOMETRY

FRAME SIZE	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	440	483	533
SEAT TUBE ANGLE (DEGREE)	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	580	595	605
REACH (MM)	406	421	431
STACK HEIGHT (MM)	605.7	605	605
HEAD TUBE LENGTH (MM)	160	160	160
HEAD TUBE ANGLE (DEGREE)	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1101	1116	1126
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	90	90
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	GREY/GREEN
SIZES	17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed, SHIMANO ALIVIO SL-M3100-L RapidFire Plus, 3-speed
FRONT DERAILLEUR	SHIMANO ACERA FD-T3000, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO ACERA FC-M371, 48-36-26T
CASSETTE	SHIMANO CS-HG200-9, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-153BT, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTS-C2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SPS 405, 27.2mm

WHEELS

FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENETR LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

superior.



Ihr Fachhändler // Votre Marchand

Hergestellt und gedruckt in der Schweiz.
Alle Angaben entsprechen dem Stand bei Drucklegung.

Irrtümer, Fehler und Änderungen vorbehalten.
Alle angegebenen Preise sind unverbindliche Empfehlungen.

Sous réserve de modification de prix et modèle.
Tous les prix indiqués sont des recommandations sans engagement.